



SPEC

DATA

This Spec-Data Sheet conforms To the editorial style prescribed by The Construction Specifications Institute. The manufacturer is Responsible for technical accuracy.

1. PRODUCT NAME

HARRICRETE ALL PURPOSE PLASTAFILLA

MANUFACTURER

HARRICRETE LIMITED.

Jankie Trace, Las Lomas #2
Republic of Trinidad and Tobago.
Tel: (868) 669-4011/4037
Fax: (868) 669-1035
E-mail: harricreteltd@gmail.com
Website: www.harricrete.com

2. PRODUCT DESCRIPTION

Harricrete all-purpose plastafilla is a smooth, non-shrink blend of the finest textured ingredients specially formulated for harsh tropical conditions. The precise manufacturing process results in combinations of chemically modified powdered polymers, producing an amazingly white "Super-Strong" filla. Harricrete plastafilla is ideal for filling cracks, holes and crevices, in walls and ceilings of wood, concrete or plaster. It forms a perfect prepared wooden surface for painting, by smooth filling all knotholes and wooden joints. Because of its long working time and excellent adhesion properties, Harricrete plastafilla can also be mixed with emulsion paint for slicking walls prior to painting. It can also be mixed with oil paint to make moisture resistant putty for use around, sinks, baths, tiles or exterior surfaces exposed to water. When dry, screws and nails can be firmly fastened so as to support light weight fixture.

3. PRODUCT BENEFITS/ADVANTAGES.

1. Non-Cracking
2. Non-Shrink
3. Extra Smooth
4. Extra Hard
5. Adequate working time
6. Snow-White

4. DIRECTIONS FOR USE

All areas to be filled or slicked must be clean and free from loose particles, dust and other contaminants that will prevent effective bonding.

1. In a clean container, mix Harricrete Plastafilla with water, until a smooth, lightly workable consistency is obtained.

For large holes or cracks, use less water to form a stiff paste for filling. Apply using similar method for pre-filling and slicking.

2. Allow to dry for 45 minutes-1hr and sand with smooth glass paper to attain desired smooth finish.

5. CAUTIONS

Do not mix more than can be applied in 30-45 minutes.
If material sets before using, do not add more water to remix. Fresh mixture should be made.

6. AVAILABILTY

In 1lb, 3lbs, 5lbs and 50lbs packages for interior and exterior application.

7. TECHNICAL SERVICES

Harricrete Ltd. offers consulting services for architects and engineers covering specifications, architectural details, technical field service, and laboratory material testing.

Manufactured by Harricrete Ltd.,
under license from DEMCO INC.,
West Des Moines, Iowa,
U.S.A.