



SPEC DATA

This Spec-Data Sheet conforms To the editorial style prescribed by The Construction Specifications Institute. The manufacturer is Responsible for technical accuracy.

1. PRODUCT NAME

HARRICRETE PLASTAMIX

MANUFACTURER

HARRICRETE LIMITED.

Jankie Trace, Las Lomas #2
Republic of Trinidad and Tobago.
Tel: (868) 669-4011/4037
Fax: (868) 669-1035
E-mail: harricreteltd@gmail.com
Website: www.harricrete.com

2. PRODUCT DESCRIPTION

Harricrete's Plastamix is a dry-packaged general purpose mortar for rendering vertical and overhead surfaces and screeds. Plastamix is a mixture of fine, clean sand and Portland Cement. Just add water to produce a smooth mortar, free from silt or stone.

The material is suitable for both minor patching and large-scale renderings. Plastermix can be used for plastering of walls of concrete, clayblock or stone.

Recommended For:

1. Small quick patching
2. Large-scale renderings
3. Use in areas where field mixes are not feasible
4. Vertical surfaces

COMPRESSIVE STRENGTH

1400 p.s.i Using 4.7 litres of water per bag

3. PRODUCT BENEFITS/ADVANTAGES.

1. Ready to use just add water
2. Non-Shrink
3. Adequate working time
4. Grey

4. DIRECTIONS FOR USE

1. Empty contents into a wheelbarrow, mortar pan, or onto smooth surface. Form a crater for water. Add 3 to 4 litres of clean water per bag and mix thoroughly. If the mortar is too stiff, add more water, a little at a time, until desired consistency is obtained. Avoid a soupy mix. Too much water will weaken the mix. Each bag will plaster approx. 1 sq. metre or 10 to 12 square feet approx. ½" of 13mm thick.

2. Apply onto desired surface. Allow to set. Scream, trowl and sponge to desired finish.

5. CAUTIONS

INJURIOUS TO EYES, CAUSES SKIN IRRITATION. Contains Portland Cement. If any cementitious material gets into the eye, flush immediately with plenty of water for at least 15 minutes. Get prompt medical attention.

Freshly mixed cement, mortar, grout or concrete causes skin irritation. Avoid direct contact where possible and wash exposed area promptly with water. Protect skin with water proof gloves or coverings.

May irritate internal tissues if ingested or inhaled. Keep out of the reach of children.

NOTE: When exposed to direct sunlight, shading is recommended to prevent cracking.

6. AVAILABILTY

In 50lbs packages (22.7 KG) for interior and exterior application.

7. TECHNICAL SERVICES

Harricrete Ltd. offers consulting services for architects and engineers covering specifications, architectural details, technical field service, and laboratory material testing.

Manufactured by Harricrete Ltd.,
Under license from DEMCO INC.,
West Des Moines, Iowa, U.S.A.